

美标截止阀
API GLOBE VALVES



GLOBE
VALVE



截止阀系列

设计特点

低泄漏控制
旋塞瓣
弹性或焊接阀座

Design Features

Low leakage control
Plug valve petal
Valve seat screw or welding

制造范围

尺寸范围：2"-24"
压力等级：ANSI 150LB-2500LB

Manufacturing Scope

Diameter: 2"-24"
Pressure: ANSI 100LB-2500LB

操作性能

阀体材料：碳钢、不锈钢、合金钢、复合钢
内件材料：按照API 600
操作方式：手动、齿轮、电动、气动

Operating Performance

Body Material: Carbon steel, Stainless steel, Alloy steel, Composite steel
Trim Material: According to API600
Mode Of Operation: Manual Operation, Gear, Electric, Pneumatic,



GLOBE VALVE

截止阀系列



+ 国标截止阀
GB Globe valve



+ 美标截止阀
API Globe valve



+ 电动截止阀
Electric Globe Valve



+ 焊接截止阀
Welded Globe Valve



+ 波纹管截止阀
Bellows Globe Valve



+ 日标截止阀
JIS Globe Valve



+ 德标截止阀
DIN Globe Valve



+ 截止阀
Globe Valve



+ 低温截止阀
Low-temperature Globe Valve



+ 保温截止阀
Thermal Insulation Globe Valve



+ 节流截止放空阀
Throttle Globe Valve



+ 衬氟截止阀
Lined globe valve



+ 锻钢截止阀
Forged Steel Globe Valve



+ 氧气截止阀
Oxygen Globe Valve

可生产阀门类型 Type of valve	通用截止阀等。 Globe valve etc.
可按各类标准生产 Standard of product	机械部标准、化工部标准、美标、日标、德标及其它非标。 JB, HG, ANSI, DIN, and other non-standard.
可生产的尺寸范围 Size range	DN15~DN600(不同阀门类型尺寸范围有所不同, 详情请电询) 2"~24" (different valve type, different size, please call for details)
可生产的压力范围 Pressure range	PN16~PN420(不同阀门类型压力范围有所不同, 详情请电询) Class 150Lb~Class2500Lb (different valve type, different pressure, please call for details)
可常用供应的阀体材料 Material of body	碳钢、不锈钢、合金钢、特种钢等。 Carbon steel, stainless steel, alloy steel, special steel etc.
可常用供应的内件材料 Material of rim	按适用介质选材 According to the medium

详细连接尺寸, 或者索要总装图, 请电询公司销售部门。
More details, pls contact our sales department.